



## RF24-105mm F4 L IS USM

- Lens control ring for fast intuitive shooting.
- 5 stop Image Stabilizer.
- Nano USM for movie shooting with a quiet and smooth AF.
- Uses a circular 9-blade aperture for exquisite soft-toned images.
- Air Sphere Coating (ASC) reduces ghosting.



## TECHNICAL SPECIFICATIONS

<b>RF24-105mm F4 L IS USM</b>		
<b>Optical Features/Specifications</b>		
	Angle of view (horzntl, vertl, diagnl)	74°, 53°, 84°
	Lens construction (elements/groups)	18/14
	No. of diaphragm blades	9
	Minimum aperture	f/4
	Closest focussing distance (m)	0.45m
	Maximum magnification (x)	0.24x
	Distance Information	Via EVF or LCD
	Air Sphere Coating (ASC)	YES
	AF actuator	Nano USM
<b>Physical Specifications</b>		
	Dust/moisture resistance	Yes <sup>1</sup>
	Filter diameter (mm)	77mm
	Max. diameter x length (mm)	83.5mm x 107.3mm
	Weight (g)	700g
<b>Accessories</b>		
	Lens cap	E-77II
	Lens hood	EW-83N
	Lens case/pouch	LP1319
	Rear cap	Lens Dust Cap RF
	Magnification with Extension Tube EF12 II	Not supported
	Magnification with Extension Tube EF25 II	Not supported
	Extender Compatibility	Not supported

<sup>1</sup> Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit  
[canon.com.au](http://canon.com.au)  
[canon.co.nz](http://canon.co.nz)

*no one sees it like you*

**Canon**